

Ancare

Disposal Station



- Large capacity HEPA filter
- Triple Blend-Activated Carbon exhaust filter
- Lighted blower and light fixture switches
- Large 40 gallon industrial strength waste container with 3" casters
- 304 stainless steel square tube frame, work surface, back and sides
- 5" stainless steel casters (2 braking)
- Powder coated steel exterior shell
- Hinged polycarbonate window
- Precision Magnehelic gauge
- Adjustable legs for comfortable work height

ANDPS363071

Ancare Corp., P.o. Box 814, Bellmore, NY, 11710
tel: 516-781-0755/800-645-6379, fax: 516-781-4937, email: info@ancare.com
www.ancare.com

Disposal Station

Features, Parts and Specifications

Specifications:

Dimensions

Overall:

36 ¼" wide x 30" deep x 75" high

Interior:

35 ¾" wide x 29 ½" deep x 22 ⅜" high

Shipping Weight

425 lbs / 195 kg

Electrical

115 volts, 60 HZ, 2 amps
10' grounded power cord

PARTS

Pre-Filter – ANDPS36FP

HEPA Filter –
ANDPS36FH

Charcoal Filter –
ANDPS36FC

Fluorescent Bulb –
ANDPS36-17Lamp

Poly liner bags - 10 rolls,
20 bags per roll - AN975

Features:

- Durable 304 stainless steel interior resists corrosion and provides an easily maintained sanitary work environment
- Rear baffle optimizes airflow and ensures even air distribution throughout work area
- Interior upper panel assembly safely contains sealed pre-filter for HEPA, HEPA filter and Triple Blend exhaust filter
- Economical, disposable pre-filter for HEPA is easily changed to enhance HEPA filter life
- Top mounted Triple Blend activated carbon exhaust filter absorbs odors and gaseous contaminants including Ammonia (NH₃)
- Large waste disposal port with removable stainless steel safety trim ring grate insert (13 ⅞" x 12" without grate, 13 ½" x 11 ½" with grate)
- Large 40 gallon industrial strength waste container
- Stainless steel aerodynamic airfoil directs uninterrupted inflow air to ensure contaminate containment
- Large 35 ¾" wide x 22 ⅜" high access opening
- Low vibration and noise levels ensures a more pleasant working environment
- Large 5" diameter corrosive resistant stainless steel casters and bearings ensure easy and quiet transportation. Two braking casters provide a stable work surface
- Precision Magnehelic gauge displays filter condition by monitoring differential pressure across the HEPA filter
- Lighted blower and lighting switches mounted on front panel for easy access
- Variable speed solid state blower control ensures that safe and efficient system airflow is maintained
- Powder coated exterior steel skin to provide a durable, maintenance free surface
- Nominal inflow velocity of 50-60 feet per minute (fpm)
- 39 watt easily accessible fluorescent fixture provides a well illuminated work area
- Work surface height is easily adjustable from 35" to 41"
- Hinged polycarbonate window provides additional visual work area and expanded access opening
- One year limited warranty